

RESIN BONDED GRINDING WHEELS WITH ALUMINIUM OXIDE

SKORPIO

flat and TOP

depressed-centre

cutting-off wheels

thickness (T)

1-1,8 mm



W D12
SS STEEL
OX
x 1,8 x 22
A46R_BF
Free of Fe+S+Cl
QS APPROVED TO ISO 9001 MADE BY COMET

SKORPIO
TOP
80 M/S
13.300 RPM
SS STEEL
INOX
x 1,6 x 22
A46R_BF
Free of Fe+S+Cl
QS APPROVED TO ISO 9001 MADE BY COMET

APPLICABLE ON:
cutting with manual
angle cutting machines with a
peripheral speed of **80 m/s**

F42

F41





Name/Quality	Quality class	Hardness	Steel	Stainless steel	Cast iron
Cutting-off wheels 20A60R_BF	TOP	Very Hard	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Cutting-off wheels 20A46R_BF	TOP	Very Hard	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>

H1	6	10	Shape	Dimensions D x T x H/mm	iT mm	Rpm m/s	Peripheral speed l/min	Packaging (units)
F41				50 x 1,0 x H1	1,15	80	30560	100
F41				50 x 1,2 x H1	1,35	80	30560	100
F41				50 x 1,6 x H1	1,75	80	30560	100
F41				50 x 1,8 x H1	1,85	80	30560	100
F41				65 x 1,0 x H1	1,15	80	24250	100
F41				65 x 1,2 x H1	1,35	80	24250	100
F41				65 x 1,6 x H1	1,75	80	24250	100
F41				65 x 1,8 x H1	1,85	80	24250	100
F41				76 x 1,0 x H1	1,15	80	20380	100
F41				76 x 1,2 x H1	1,35	80	20380	100
F41				76 x 1,6 x H1	1,75	80	20380	100
F41				76 x 1,8 x H1	1,85	80	20380	100
F41				100 x 1,0 x 10	1,15	80	15280	25
F41				100 x 1,0 x 16	1,15	80	15280	25
F41				100 x 1,2 x 16	1,35	80	15280	25
F41				100 x 1,6 x 16	1,75	80	15280	25
F41				100 x 1,8 x 16	1,85	80	15280	25
F41				115 x 1,0 x 22	1,15	80	13280	25
F41				115 x 1,2 x 22	1,35	80	13280	25
F41				115 x 1,6 x 22	1,75	80	13280	25
F42				115 x 1,6 x 22	1,75	80	13280	25
F41				115 x 1,8 x 22	1,85	80	13280	25
F41				125 x 1,0 x 22	1,15	80	12200	25
F41				125 x 1,2 x 22	1,35	80	12200	25
F41				125 x 1,6 x 22	1,75	80	12200	25
F42				125 x 1,6 x 22	1,75	80	12200	25
F41				125 x 1,8 x 22	1,85	80	12200	25
F41				150 x 1,6 x 22	1,75	80	10190	25
F41				150 x 1,8 x 22	1,85	80	10190	25
F41				178 x 1,6 x 22	1,75	80	8600	25
F41				178 x 1,8 x 22	1,85	80	8600	25
F41				230 x 1,6 x 22	1,75	80	6600	25
F41				230 x 1,8 x 22	1,85	80	6600	25
F42				230 x 1,8 x 22	1,85	80	6600	25

1. very narrow cut


BETTER MATERIAL EFFICIENCY

2. a shorter duration of cutting

TIME SAVINGS

3. minimum overheating of cut workpieces

C O M E T



Umetni brusni in nekovine, d.d.
Tovarniška 5, 3214 Zreče, Slovenia
<http://www.comet.si> E-mail: comet@comet.si
Tel.: +386 3 7575 000
Fax: +386 3 7575 100

